

Sophos SD-RED



Zero-touch edge and branch connectivity

SD-RED offers a uniquely simple solution to extend network connectivity to your remote locations and branch offices, no matter where in the world they are. Replace expensive MPLS connections to reduce your costs and take advantage of other Sophos products, such as Intercept X, for added SD-WAN functionality in combination with Sophos Firewall.

Plug-and-protect deployment

Sophos SD-RED makes extending your secure network to other locations easy. It requires no technical skills at the remote site; simply enter the device ID into your Sophos firewall appliance and ship it. As soon as the device is plugged in and connected to the internet, it will contact your firewall and establish a secure dedicated VPN tunnel. It's really that simple.

Flexible configuration

Set up your SD-RED devices to tunnel all traffic from the remote location back to the firewall, controlling DHCP and other network elements of the remote network. Or, you can choose to only route inter-office network traffic via your SD-RED, while enabling direct internet access from the remote location.

Securely encrypted, centrally managed

All data between the SD-RED and your Sophos firewall is encrypted using AES-256 levels, ensuring a tamper- and hack-proof, secure connection. With central management from our XGS and SG Series, protection is completely transparent across your distributed network and can be customized or replicated to suit your needs.

Synchronized SD-WAN


When managed through Sophos Firewall OS (SFOS), Synchronized SD-WAN allows you to benefit from the power of Synchronized Security and SFOS's integration with Sophos Intercept X to optimize WAN path selection for your important business applications with 100% reliability.

Flexible Wi-Fi and WAN connectivity

Optionally add a Wi-Fi-5 or 3G/4G module to provide connectivity for wireless clients or to use 3G/4G internet connections.

Highlights

- ▶ Easily extend your secure network to any location
- ▶ Select from two models to suit your deployment and connectivity needs
- ▶ Use strong AES 256-bit encryption
- ▶ Seamlessly connect with Sophos APX Access Points
- ▶ Benefit from Synchronized SD-WAN with Sophos Firewall and Intercept X



Choose your RED

Our SD-RED devices are built on the latest enterprise-class, high-speed networking platforms. They work with your Sophos (SG) UTM/Firewall appliance (hardware, software, virtual, or cloud). Our range of Sophos APX Series Access Points are also compatible with Sophos SD-RED for secure, high-speed wireless connectivity.

Licensing

To manage a Sophos SD-RED you will need an active Network Protection subscription for either Sophos UTM or Sophos Firewall. To use Wi-Fi with UTM, you will additionally need a valid UTM Wireless Protection subscription.

Technical specifications

Model Name	SD-RED 20	SD-RED 60
Product Support Added	SFOS 17.5 MR 11, SFOS 18.0 MR 1, UTM 9.7 MR 3	
Maximum Throughput	250 Mbps	850 Mbps
PHYSICAL INTERFACES (BUILT-IN)		
LAN Interfaces	4 x 10/100/1000 Base-TX (1 GbE Copper)	
WAN Interfaces	1 x 10/100/1000 Base-TX (shared with SFP)	2 x 10/100/1000 Base-TX (WAN1 shared port with SFP)
SFP Interfaces	1x SFP Fiber (shared port with WAN)	1x SFP Fiber (shared port with WAN1)
Power-over Ethernet Ports	None	2 PoE Ports (total power 30W)
USB Ports	2 x USB 3.0 (front and rear)	
COM Ports	1 x Micro-USB	
OPTIONAL CONNECTIVITY		
Modular Bay	1 (for use with optional Wi-Fi OR 4G/LTE Card)	
Optional Wi-Fi Module	802.11 a/b/g/n/ac Wave 1 (Wi-Fi 5) dual-band capable 2x2 MIMO 2 antennas	
Optional 3G/4G LTE Module	MC7430/MC7455 Sierra Wireless Card	
Optional VDSL Modem	Optional SFP Modem (support in an upcoming release)	
PHYSICAL SPECIFICATIONS		
Dimensions	225 x 44 x 150 (w*h*d) mm 8.86 x 1.73 x 5.91 (w*h*d) inches	225 x 44 x 150 (w*h*d) mm 8.86 x 1.73 x 5.91 (w*h*d) inches
Weight	0.9 kg/1.8 kg (1.98 lbs/3.97 lbs) Unpacked/Packed	1.0 kg/2.2 kg (2.2 lbs/4.85 lbs) Unpacked/Packed
Power Redundancy Support	Yes, optional 2nd power supply	Yes, optional 2nd power supply
Power Consumption	Idle: 6.1Watt/20.814 BTU Full Load: 22.6Watt/77.114 BTU	Idle: 11.88 Watt/40.536 BTU Full Load without PoE: 25.33 Watt/86.429 BTU Full Load with PoE: 62.48 Watt/213.190 BTU
Temperature (operational)	0°C to 40°C (32°F to 104°F)	
Temperature (storage)	-20°C to 70°C (-4°F to 158°F)	
Humidity	10-90% RH, non-condensing	
Certifications (Safety, EMC, Radio)	CE/FCC/IC/RCM/VCCI/CB/UL/CCC/KC/ANATEL	



Try it now for free

Register for a free 30-day evaluation at sophos.com/firewall

United Kingdom and Worldwide Sales
Tel: +44 (0)8447 671131
Email: sales@sophos.com

North American Sales
Toll Free: 1-866-866-2802
Email: nasales@sophos.com

Australia and New Zealand Sales
Tel: +61 2 9409 9100
Email: sales@sophos.com.au

Asia Sales
Tel: +65 62244168
Email: salesasia@sophos.com